

Shot ID	Club Type	Club ID	Ball Speed	Launch Angle	Side Angle	Side Spin	Back Spin	Tilt Angle	Total Spin	Peak Height	Carry	Range	Offline	Descent Angle
1	Driver	915d3 9.5 stiff	137.4	9.3	-12.7	-80	2708	-1.7	2709	19.8	216	209.8	-50	30.7
2	Driver	915d3 9.5 stiff	136.9	15.1	0.1	1086	3599	16.8	3759	34.1	211	209	30.9	44.6
3	Driver	915d3 9.5 stiff	144.7	10.7	-7.5	-1678	1701	-44.6	2389	15.7	201	187.7	-72.5	29
4	Driver	915d3 9.5 stiff	133.4	16.4	-3.3	-460	2609	-10	2649	33.5	220	218	-29.8	41.7
5	Driver	915d3 9.5 stiff	136.7	12.7	-7.9	-1235	1880	-33.3	2249	20.5	209	197	-69	33.7
6	Driver	915d3 9.5 stiff	140	11.9	-2.6	-927	2186	-23	2374	22.9	223	218.2	-44.2	33.6
7	Driver	TS2 9.5 st A1	146.2	12.2	-3.8	-598	1429	-22.7	1549	20.4	239	235.2	-43.3	26.9
8	Driver	TS2 9.5 st A1	140.4	17.1	1.4	266	2772	5.5	2785	40.2	234	233.7	16.3	45
9	Driver	TS2 9.5 st A1	142.8	13.8	-5.5	220	2741	4.6	2750	33.3	237	237.1	-13.9	39.9
10	Driver	TS2 9.5 st A1	146.7	12.8	-5.5	76	1898	2.3	1900	27.5	254	253.5	-20.4	33
11	Driver	TS3 9.5 stiff A1	144.3	13.7	-2.5	1207	3354	19.8	3565	33.7	225	223.2	28.7	43.9
12	Driver	TS3 9.5 stiff A1	146.6	14.7	-5.5	-1078	1181	-42.4	1599	22.9	232	221.4	-68.1	32.1
14	Driver	TS3 9.5 stiff A1	145.7	14.4	-1.6	1320	3051	23.4	3324	34.7	229	226	38.6	44.4
15	Driver	TS3 9.5 stiff A1	140.6	13.1	-3.4	29	1699	1	1699	24.5	241	240.5	-12.9	30.1
16	Driver	TS3 9.5 stiff A1	143.2	15.1	-3.2	-124	1695	-4.2	1700	30.5	254	253	-21.1	34.8
18	Driver	G400 9.5 stiff	140.3	15.5	-2.5	856	2927	16.3	3050	35.6	227	225.7	20.6	43.1
21	Driver	G400 9.5 stiff	147.5	11.6	-4.2	726	3121	13.1	3204	30.6	236	236	8.7	39.3
22	Driver	G400 9.5 stiff	146.9	12.3	-6.6	-906	1526	-30.7	1775	21	235	225.5	-65.3	29.9
23	Driver	G400 9.5 stiff	143.3	16.7	-3	171	2644	3.7	2650	40.6	243	242.7	-5.2	43.9
25	Driver	G400 9.5 stiff	135.1	19.5	-1.7	-752	3801	-11.2	3875	43.7	208	206.4	-27.2	49.7
26	Driver	G400 9.5 stiff	141.5	12.4	2.2	1052	3022	19.2	3200	28.4	222	218.1	42.5	39.7
27	Driver	TS2	145	12.3	-4.1	370	2740	7.7	2765	30.5	239	239.3	-2.2	38
28	Driver	TS2	144	13.3	-3.3	1087	2892	20.6	3090	31.1	229	227.6	25	40.8
30	Driver	TS2	147.4	11.2	0.7	1094	2991	20.1	3185	27.9	232	228.2	40.5	39.2
31	Driver	TS2	143.9	13.7	2.3	847	2789	16.9	2915	32.6	234	230.1	41.2	41.3