

CLUB	CLUB HEAD SPEED		BALL SPEED	EFFICIENCY	LAUNCH ANGLE	AZIMUTH	SIDE SPIN	BACK SPIN	TOTAL SPIN	PEAK HEIGHT	DESCENT ANGLE	CARRY
	MPH	MPH	RATIO	(°)	(°)	RPM	RPM	RPM	YDS	(°)	YDS	YDS
4 iron	87.9	119.5	1.36	15.1	4.7	240L	3627	3635	25	39	180	197
Average	89.1	121.1	1.36	14.5	4.3	302L	3755	3798	25	39	181	198
20 degree hybrid	85.9	120.3	1.40	15.0	2.1	513L	2615	2665	23	35	187	210
20 degree hybrid	89.4	125.2	1.40	13.3	5.4	316L	3345	3360	24	37	192	212
20 degree hybrid	90.8	127.2	1.40	11.5	1.9	943L	3334	3465	21	34	189	211
Average	88.7	124.2	1.40	13.3	3.1	590L	3098	3163	23	35	189	211
17 degree hybrid	88.7	124.2	1.40	12.8	5.1	797L	1444	1650	15	24	183	218
17 degree hybrid	92.9	130.0	1.40	12.2	7.9	45L	3249	3250	24	36	202	222
17 degree hybrid	93.2	130.4	1.40	10.7	1.9	1123L	1891	2200	14	24	188	223
Average	91.6	128.2	1.40	11.9	5.0	655L	2194	2366	18	28	191	221
3 wood	82.3	119.3	1.45	18.2	7.5	774L	1935	2085	26	36	191	215
3 wood	84.3	122.2	1.45	15.1	4.8	1143L	1995	2300	20	32	185	211
3 wood	90.8	131.7	1.45	13.0	5.9	970L	2140	2350	21	31	205	233
Average	85.8	124.4	1.45	15.4	6.1	962L	2023	2245	23	33	194	220
Driver	90.7	131.5	1.45	15.7	0.6	234L	1860	1875	27	35	223	250
Driver	90.3	131.0	1.45	14.6	-3.3	137R	1970	1975	25	34	219	246
Driver	95.2	138.0	1.45	13.6	2.2	138L	2481	2485	29	37	229	253
Average	92.1	133.5	1.45	14.6	-0.2	78L	2103	2111	27	35	224	250

